

Oli Motore: Mobil Delvac 1

Mobil Delvac



Mobil Delvac 1™ LE 5W-30

Mobil Delvac 1™ 5W-40

Mobil Delvac 1™ SHC 5W-40

Soddisfa o supera i requisiti di

ACEA	E7/E6/E9	E7/E4	E4
API	CJ-4/SN	CI-4/CH-4/CI-4 PLUS/SL/SJ	
Caterpillar	ECF-3		
Cummins	CES 20081	20078/77/76/75	
DAF	Extended Drain		
Ford	WSS-M2C171-E	WSS-M2C171-D	
ACEA/EMA/JAMA		Global DHD-1	
JASO	DH-2	DH-1	
Renault Trucks		RXD	

Approvazioni

Detroit	Fluid Specification 93K218	Fluid Specification 93K214	
Deutz	DQC IV-10 LA		
Mack	EO-O Premium Plus	EO-N Premium Plus 03, EO-M Plus	
MAN	M 3677/M 3477/MAN M3271-1		M 3277
MB	Approval 228.51/228.31/235.28	Approval 228.5/235.28	Approval 228.5
MTU	Oil Category 3.1		Oil Category 3
Renault Trucks	RLD-3/RLD-2		
Scania		LDF	
Volvo	VDS-4/VDS-3	VDS-3/VDS-2	
ZF			

E' consigliato dalla ExxonMobil per l'utilizzo in applicazioni che richiedono

API		CG-4/CF-4/CF	CF
Caterpillar		ECF-1	
Cummins		CES 20072/71	
Renault Trucks	RXD/RGD		
Volvo			VDS-2

Oli Motore: Mobil Delvac

Mobil Delvac



Mobil Delvac™ XHP Ultra 5W-30 Mobil Delvac™ XHP ESP 10W-40 Mobil Delvac™ XHP Extra 10W-40

Soddisfa o supera i requisiti di

ACEA	E4	E7/E6/E4	E7/E4
API		CI-4	
Caterpillar			
Cummins			
DAF		Extended Drain	
JASO		DH-2	
Renault Trucks		RXD/RLD-2/RGD	RXD

Approvazioni

Detroit			
Deutz		DQC IV-10 LA	
Ford		WSS-M2C944-A	
Mack			
MAN	M 3277	M 3477	M 3277
MB		Approval 228.51/228.5/235.27	Approval 228.5/235.27
MTU	Oil Category 3	Oil Category 3.1	Oil Category 3
Scania		Low Ash	LDF-3/LDF-2
Voith			Oil Class B
Volvo		VDS-3	VDS-3/VDS-2
ZF			TE-ML 04C

E' consigliato dalla ExxonMobil per l'utilizzo in applicazioni che richiedono

ACEA			
API			CF
Cummins			CES 20072
Detroit			
MAN		M 3277(CRT)	
Renault Trucks			
MB	Approval 228.5		

Oli Motore: Mobil Delvac



Mobil Delvac™
MX Extra 10W-40

Mobil Delvac™
MX ESP 15W-40

Mobil Delvac™
MX 15W-40

Mobil Delvac™
MX ESP 10W-30

Soddisfa o supera i requisiti di

ACEA	E7	E9/E7	E7	E9/E7
API	CI-4/CH-4/SL/SJ	CJ-4/CI-4 PLUS/CI-4/CH-4/SM/SL	CI-4/CH-4/SL/SJ	CJ-4/CI-4 PLUS/CI-4/CH-4/SM
Caterpillar		ECF-3	ECF-2	ECF-3
Isuzu				
Cummins	CES 20078/77/76	CES 20081	CES 20077/76	CES 20081
ACEA/EMA/JAMA				
JASO		DH-2		DH-2
Renault Trucks	RLD-2/RLD	RLD-3		



Approvazioni

Detroit		Fluid Specification 93K218/93K214		
Deutz		DQC II-10 LA		DQC II-10 LA
Mack	EO-M PLUS	EO-O Premium Plus, EO-N Premium Plus, EO-N Premium Plus 03	EO-M Plus/EO-N	EO-O Prem Plus
MTU	Oil Cat. 1 - Open Crank, ODI up to 500 Hrs			
MAN	M 3275-1	M 3575	M 3275-1	M 3575
MB	Approval 228.3/235.28	Approval 228.31	Approval 228.3	Approval 228.31
Allison		TES-439		
Volvo	VDS-3/VDS-2	VDS-4/VDS-3/VDS-2	VDS-3	VDS-4/VDS-3
Renault			RLD-2	RLD-3

E' consigliato dalla ExxonMobil per l'utilizzo in applicazioni che richiedono

ACEA	B2, A2		A2, B2	
API	CF	CG-4/CF-4/CF-2/CF	CG-4/CF-4/CF	CG-4/CF
Cummins	CES 20072/71		CES 20072/71	
Detroit	7SE270 (4-STROKE CYCLE)		7SE270 (4-STROKE CYCLE)	
Allison				

Oli per Ingranaggi



Mobilube 1 SHC™ 75W-90

Mobil Delvac™ Synthetic Gear Oil 75W-90

Mobil Delvac™ Synthetic Gear Oil 75W-140

Soddisfa o supera i requisiti di

API	GL-5/MT-1	GL-5/MT-1	GL-5
Scania	STO 1:0	STO 2:0 A	STO 2:0 A
ZF	TE-ML 07A/08	TE-ML 07A/08	




Approvazioni

ArvinMerritor		0-76N	
Dana		SHAES 256 Rev C, SHAES 429	
Flender		BA 7302 Table R1	
International		TMS-6816	
JSC Avtodizel	YaMZ Gearboxes		
Mack		GO-J PLUS	
MAN	341 Typ E3/Z2, 342 Typ M3	342 Typ M2	
MB	Approval 235.8	Approval 235.8	
SAE Grade	J2360	J2360	
Scania		STO 2:0 A	STO 2:0 A
Voith Turbo		132.00374401 / 132.00374402	
Volvo		97312	
ZF	TE-ML 02B/05B/12B/16F/17B/19C/21B	TE-ML 05B/12B/16F/17B/19C/21B	

E' consigliato dalla ExxonMobil per l'utilizzo in applicazioni che richiedono

API	GL-4		
Eaton		PS-163	
US Military		MIL-PRF-2105E quality level but not approved	
ZF			

Oli per Ingranaggi



Mobiltrans™ MBT 75W-90

Mobilube™ HD-A Plus 80W-90

Mobilube™ HD-A 85W-90

Soddisfa o supera i requisiti di

API		GL-5	GL-5
Scania		STO 1:0	
ZF		TE-ML 07A	TE-ML 07A




Approvazioni

ArvinMerritor			
Dana			
Flender			
International			
JSC Avtodizel			
MB	Approval 235.11	Approval 235.20	Approval 235.0
Mack			
MAN		342 Typ M3	342 Typ M1
Voith Turbo			
ZF		ZF TE ML 05A/12E/16B/17B/19B/21A	TE-ML 16C/17B/19B/21A

E' consigliato dalla ExxonMobil per l'utilizzo in applicazioni che richiedono

API			
Eaton			
MIL			

Oli per Ingranaggi e Trasmissioni



Mobil Delvac™ Synthetic ATF	Mobil Delvac™ Synthetic Transmission Oil V30	Mobil Delvac™ XHP Transmission Oil 75W-80	Mobilube™ S 80W-90
-----------------------------	--	---	--------------------

Soddisfa o supera i requisiti di

API			GL-5/MT-1
Scania			STO 1:0
ZF			TE-ML 07A/08

Approvazioni

Allison	TES-295 (AN - 051005)		
Mack			GO-J
MAN		341 Typ E4	341 Typ E3/Z4
MB	Approval 236.91		Approval 235.0
Voith Turbo	H55.633639 DIWA Service Bulletin 118/013 Extended Drain		
Volvo		97307	
ZF	TE-ML 04D/14C/16M/20C		ZF TE-ML 01L/02L/16K
			ZF TE-ML 02B/05A/12E/12L/12M/16B/17B/19B/21A

E' consigliato dalla ExxonMobil per l'utilizzo in applicazioni che richiedono

API			GL-4
ArvinMerritor			076-D
US Military			
MAN			
ZF			TE-ML 08